




Performance Analysis — 3
Expected performance — 7
Robustness — 18




Performance Analysis

Safety Assessment

→ SC1 (2019)




→ SC2 (2023)



Performance Analysis: *containment*

objectives

1. Quantify the **expected containment performance** of the disposal system and of its components and safety functions
2. Demonstrate that the disposal system and its components are **robust** against possible threats/perturbations
3. Demonstrate that the containment performance is **commensurate with the risks** posed by the waste





→ **defence-in-depth principle**



Expected performance

Expected evolution: EES





earth cover

cover

impervious top slab

monoliths

module

(sand) side embankment


Inspection gallery

Inspection room



Foundations (incl. sand-cement embankment)

Performance Analysis model

TI - initial TIII - initial



- redistribution layer
- concrete
- mortar
- waste form
- inspection room backfill
- embankment
- inter-monolith space
- fracture



sck

Performance indicators / output

Indicators

- **PI1**: decayed fraction in component
- **PI2**: activity/radiotoxicity in component
- **PI3**: concentration profiles
- **PI4**: flux between components
- **PI5**: flux out of disposal system
- **PI6**: cumulative flux out of disposal system
- **PI7**: residence time in component / containment factor


Activity distribution

- 100% in Type I monoliths
- 100% in Type III monoliths
- Weighted: 76% in Type I
24% in Type III



Sorption classes (on HCP)

- Class I: $K_d \leq 10^{-2} \text{ m}^3/\text{kg}$ (e.g. Be, I, Cs)
- Class II: K_d in between (e.g. Ca, Cl, Ni)
- Class III: $K_d \geq 1 \text{ m}^3/\text{kg}$ (e.g. Nb, Pd, act)


Limitation of water infiltration in modules (R2a)




Diversion of water away from the waste (R2a)



1. Preferential flow between monoliths
2. Avoid bath-tubbing by proper drainage in module base



Containment inside monoliths (R1/R3/R4a)




SORPTION

**Activity in monolith
after 2000 a**

	% decay	waste	mortar	caisson	total
^{10}Be	<0.01%	<0.01%	<0.01%	<0.01%	<0.01%
^{129}I	<0.01%	2.9%	1.1%	0.3%	4.2%
^{59}Ni	1.8%	74.0%	12.0%	2.5%	90.3%
^{239}Pu	5.6%	92.9%	1.4%	0.1%	~100%


Containment outside monoliths (R3/R4b)



- Radionuclides that end up in fractures or the inter-monolith space (IMS) are further transported by advection
- Releases from the disposal system are still spread in time by dispersion in **Conductive Sorbing Media (CSM):**
 1. Grout backfill in inspection room
 2. Sand-cement in embankment, inspection gallery and connecting tunnels



Containment outside monoliths (R3/R4b)

Role of conductive sorbing media



- Non-sorbed radionuclides **shortly accumulate** in CSM and are soon released again
- Moderately sorbed radionuclides are delayed, but reach a **plateau** (supply \approx discharge)
- Well-sorbed radionuclides **accumulate** in the inspection room

Expected containment performance






Robustness

Robustness against *threats*

1	Threats directly compromising the <i>protective</i> role of the earth cover	<ul style="list-style-type: none"> Erosion (AES3-1, AES3-2) Crash of small aircraft (AES2-1) Earthquake (AES1-1) 	<ul style="list-style-type: none"> Early gradual degradation
2	Threats causing a direct and <i>abrupt</i> degradation of cementitious SSCs	<ul style="list-style-type: none"> Crash of a large aircraft (AES2-2) Heavy earthquake (AES1-2) Large scale excavation (HIS excav) 	<ul style="list-style-type: none"> Early abrupt degradation 50% water flow in monolith fractures Extra fracture in Type I monoliths
3	Threats causing a <i>bypass</i> of SSCs that normally contribute to the containment capacity	<ul style="list-style-type: none"> Borehole drilling (HIS drill) 	<ul style="list-style-type: none"> Bypass of CSM (all monoliths in affected module) Same as 2 (pierced stack)
4	Threats causing <i>internal</i> perturbations	<ul style="list-style-type: none"> undetected complexants in the waste form (AES4) 	<ul style="list-style-type: none"> 1% of the waste with zero sorption

Impairment of the cover




Cumulative released RT	EES	AES1-1	AES2-1	AES3-1
% of initial RT	0.0068	0.0102	0.0093	0.0084
% residual RT	0.48	0.72	0.65	0.59

Performance loss of the cover is compensated by:

- Efficient water diversion away from the waste (R2a)
- Slow release from the waste form (R1/R3)
- Dispersion in conductive sorbing media (R4b/R3)

Abrupt and extreme degradations




Cumulative released RT	EES	AES1-2	AES2-2	HIS excav
% of initial RT	0.0068	0.0302	0.0193	0.0302
% residual RT	0.48	2.13	1.36	2.13

Performance loss of cementitious barriers is compensated by:

- Slow release from the waste form (R1/R3)
- Dispersion in conductive sorbing media (R4b/R3)

Role of conductive sorbing media (bis)


Sorption class III nuclides in Type I monoliths



Theoretical transport time [a]

SORPTION	K_d [m ³ /kg]	Inspection room 60 cm thick	Embankment 2 m thick
	0	< 1 a	< 1 a
0,1	17 a	37 a	
0,5	84 a	185 a	
1	167 a	370 a	
10	1 668 a	> 2 000 a	

Bypass of conductive sorbing media (CSM)




Cumulative released RT	EES	HIS drill
% of initial RT	0.0068	0.0084
% residual RT	0.48	0.59

Performance loss through bypass of CSM is compensated by:

- Efficient water diversion away from the waste (except for the pierced monolith stack) (R2a)
- Slow release from the waste form (R1/R3)

Internal disturbances (complexants)



Cumulative released RT	EES	AES4
% of initial RT	0.0068	0.0252
% residual RT	0.48	1.77

Local loss of sorption capacity due to undetected presence of complexants is compensated by:

- Protection by the cover (no *early* degradation)
- Efficient water diversion away from the waste (R2a)
- Slow release from the waste form and slow diffusion in the concrete/mortar matrix (R1/R4a)

Conclusions of FANC / Bel-V

R-SER-22-043-0-n

ONDRAF/NIRAS has performed a detailed performance analysis in which

- The complementarity of barriers and/or safety functions is demonstrated
- The disposal system shows an adequate level of robustness against reasonably foreseeable threats
- The performance of the disposal system is commensurate with the risks posed by the waste


Conclusions of FANC / Bel-V

R-SER-22-043-0-n

The safety authority further asks to

- Update the impact analysis using the PA-model (one model for all)
- Evaluate the *bypass* potential for well-sorbed (class III) radionuclides in Heterogenously Cemented waste (HEC)

A potential “bypass” in HEC waste?



- To which degree can the sorption capacity in the conditioning mortar be bypassed by *well-sorbed* radionuclides that require some time to dissolve?
- Dedicated, representative model(s) in development...

The PA team

sck cen

Joan Govaerts

Janez Perko

Eef Weetjens

Diederik Jacques



Elise Vermariën

References

**SCK CEN report ER-0601
(OD-284)**

**§14.14 and §2.9
of the Safety Report**

Copyright © SCK CEN

PLEASE NOTE!

This presentation contains data, information and formats for dedicated use only and may not be communicated, copied, reproduced, distributed or cited without the explicit written permission of SCK CEN.

If this explicit written permission has been obtained, please reference the author, followed by 'by courtesy of SCK CEN'.

Any infringement to this rule is illegal and entitles to claim damages from the infringer, without prejudice to any other right in case of granting a patent or registration in the field of intellectual property.

SCK CEN

Belgian Nuclear Research Centre

Foundation of Public Utility

Registered Office: Avenue Herrmann-Debrouxlaan 40 – BE-1160 BRUSSELS

Operational Office: Boeretang 200 – BE-2400 MOL