

OBSERVATIONS during 10 years of heating

Can the clay withstand the thermal load from heat-emitting waste?

T. Georgieva, A. Dizier, J. Verstricht, D. Nackaerts, S. Levasseur

EURIDICE










PHASES of the PRACLAY EXPERIMENT








OUTLINE

- Heater Test Steering parameters
- Observations
 - Boom Clay
 - > Test set-up (Seal/ Concrete lining)
- Conclusion

Monitoring set-up









Heating the clay to 80°C














Stable heating at 80°C during 10 years

Temperature at the concrete/clay interface



Ring 50 CG T-Thermocouples









Temperature is uniform along the PG lining

Temperature profiles in concrete lining along the PG at the end of stationary heating













Excess pwp induced by the thermal loading

Pore water pressure (pwp) inside the PG











OUTLINE


- Heater Test Steering parameters
- Observations
 - Boom Clay
 - > Test set-up (Seal/ Concrete lining)
- Conclusion



OPENING THE COOLING PHASE



What do we observe in the clay?













Temperature in the Boom Clay along the PG

Temperature profiles in borehole CG35E at various times



CG35E: ~2 m from PG → perturbed zone











Temperature evolution in time

Various horizontal distances from the PG











Pore water pressure evolution

Pore water pressure in function of time













Effects in function of horizontal distance to PG

Temperature profiles



Pore water pressure profiles











Temperature profiles during steady state

Horizontal versus vertical













Vertical vs horizontal boreholes

Temperature evolution













Vertical vs horizontal boreholes

Pore water pressure evolution





OPENING THE COOLING PHASE









Total pressure in the clay: 9 m from the PG

Total pressure



Variation of total pressure










Does the clay withstand the thermal load?

- Pore water pressure observation → no sudden changes
- Damages → modification of permeability

Permeability tests shortly after the excavation of the Connecting Gallery











Does the clay withstand the thermal load?

Temperature profiles



Intrinsic permeability profiles









OUTLINE


- Heater Test Steering parameters
- Observations
 - **Boom Clay**
 - > Test set-up (Seal/ Concrete lining)
- Conclusion






What do we observe in the seal and the concrete lining?

Seal



Concrete lining
















At Boom Clay/ bentonite interface














Total pressure evolution at in the seal



At Boom Clay/ bentonite interface


















At bentonite/steel cylinder interface













Displacement of the seal

Section A Section B

Towards the Connecting Gallery














Observations in the lining: non-heated part



Total pressure in the non-heated part (Ring 12)



Circumferential stress in the non-heated part (Ring 12)




Concrete lining: C80/95









Observations in the lining: heated part



Total pressure in the heated part (Ring 46)



Circumferential stress in the heated part (Ring 46)



Concrete lining: C80/95







27



OUTLINE

- Heater Test Steering parameters
- Observations
 - Boom Clay
 - > Test set-up (Seal/ Concrete lining)
- Conclusion





CONCLUSIONS

- No interruption of the heater system
- → good performance of the test set-up
- Boom Clay is able to withstand the thermal loading
 - ✓ No indication of abrupt changes in pore water pressure nor large displacement.
 - ✓ No changes in the intrinsic permeability
 - ✓ Anisotropic responses, as expected (vertical vs horizontal profiles)
- Seal fulfils its role as a hydraulic cut-off
- Stresses in the lining remain well below the ultimate strength
- → Important input for THM knowledge and repository design











OPENING THE COOLING PHASE